



# Mini Bar® Double

## 2-Level 2 Chargers & 2-Level 1 Convenience Connections

A 2015 Winner of NECA Showstopper New Product Showcase

### PREMIUM ELECTRIC VEHICLE CHARGING PRODUCT & EXPERIENCE



#### Mini Bar - Technical Specifications

Two Level 2 Chargers & Two Level 1 Convenience Connections

Certifications	IP Rating
ETL Listed	NEMA 3R
AC Input From Utility – Level 2	Operating Temperature
Voltage 208/240 VAC Breaker Rating 40A – requires 2	-30° C to 55° C (-22° F to +122° F)
AC Output to Vehicle – Level 2	Communications
Voltage 208/240 VAC 32A (7.7kW max) each side	Ethernet or Cellular
AC Input – Level 1 (not managed by software, option to lock off)	
Voltage 120 VAC Breaker Rating 20A – requires 2	
Dimensions	
60" total height with Pedestal 36.5" total height w/out Pedestal, as wall mount option	16" Width (36" with connectors plugged in on each side) 12 3/8" Depth
Connector – Level 2	Cord Length
SAE compliant J1772 Connector	23 feet
Unit Material	
Powder Coated Aluminum	Pedestal is Powder Coated Steel

**Model numbers:**

**MB402-1.0 Mini Bar Double**

**MB402C-1.0 Mini Bar Double with Communication/Revenue Management System** – station does not need to be networked or software activated for the charger to work.

**Options Available:**  
Cord Management System  
Pedestal or Wall Mount  
"Tough" Connector – see back for details

Garage Juice Bar LLC  
One Technology Drive  
Tolland, CT 06084  
860-308-2054

## Mini Bar Features

Made in  
USA

Fully  
Customizable for  
branding,  
sponsors and  
advertising

Innovative  
Illuminated  
Customizable  
Wall Mount or Pedestal  
Weatherproof/Indoor/Outdoor Use  
Premium Product & Experience  
LED indicator lights  
Visually appealing – Attracts Attention  
Cut down on installation costs, 4 charger connections one installation  
36 Month Limited Warranty on Level 2 charging component,  
1 Year Limited Warranty on rest of components  
Customer Service – US based company  
Extended Warranties and/or Maintenance Programs Available  
Communications & Revenue Management System(optional)

- Open standards – based solution- powered by Greenlots
- Highest level of choice to site hosts
- Flex pricing – different prices for time of day & day of week
- Remotely monitor all EV charging experiences
- No more RFID cards, use QR scan code or input station id
- Mobile App with many features
- Load Management and Load Sharing Capabilities

greenlots®



### NEW OPTION

**“TOUGH CONNECTOR”**  
J1772 Connector & Cable.  
Type 4X watertight and corrosion resistant rubber overmolded EV connector. Impact & crush resistant with a field replaceable latch.  
**5 year warranty** (on this option, only for connector/cable/charging component)

CALL FOR DETAILS

### Wall Mount

